## ROG SWIFT PRO



## PG248QP E-sport Gaming Monitor



## KEY FERTURES



Features 540Hz (OC) refresh rate for ultra fast and smooth gameplay



With up to 50% faster performance than 360Hz IPS panel, the E-TN panel sets a new standard



With a 0.2ms response time, smearing and motion blur are virtually eliminated



Delivers a seamless, tear-free gaming experience with GeForce® graphics cards



Immersive gaming audio is enabled via an integrated ESS codec



Enjoy near-zero latency, surround sound, and enhanced audio for heightened in-game awareness



Ambient lighting on the back of the monitor that can be synchronized with connected Auraenabled peripherals



Ensures smoother color gradation delivered, uniformity and the △E color difference value is less than 2



With a peak brightness of 400 nits, the PG248QP meets the requirement for DisplayHDR™ 400 certification



ROG Swift Pro PG248QP has undergone stringent performance tests and is certified Flicker-free and Hardware Low Blue Light by TÜV Rheinland laboratories, a global provider of technical, safety, and certification services

## ROG SWIFT PRO PG248QP



Display	Panel Size (diagonal)		24.1" Wdie Screen
	Display Viewing Area		535.68 x 298.08 mm
	Panel Backlight/ Type		Esports TN
	Display Surface		Non-glare
	Color Saturation		sRGB 125%
	True Resolution		1920 x 1080
	Refresh rate		540Hz (OC)
	Pixel Pitch		0.277 mm
	Brightness		400cd/㎡ (typ.)
	Contrast Ratio		1,000:1 (Typ.)
	Viewing Angle (CR≥10)		170°/ 160°
	Display Colors		16.7M
	Response Time		0.2ms (min.)
	HDR Support		Yes, HDR 10
Video Features	Factory pre-calibration		Yes
	GamePlus		Yes
	GameVisial		Yes
	ULMB 2		Yes*
	VRR		Yes, G-Sync
ESS		DAC	Yes
	Input /	Output	1xDisplayPort v1.4, 2x HDMI v2.0 , 2xUSB 3.2 Gen 1 Type-A, earphone jack
Signal Frequency		Digital Signal Frequency	HDMI: 24-240Hz(V)/30-255KHz(H)DP: 1-510Hz(V)/510- 510KHz(H)
Power		Power Consumption	<21W**
		Voltage	100-240V, 50 / 60 Hz
Mechanical Design		Tripod socket	Yes
		Height adjustment	110mm
		Swivel	-30° ~ +30°
		Tilt	-5° ∼ +20°
		VESA Mount	100 x 100 mm
Dimension		Phy. Dimension	557.3 x (392.2~502.2) x 254.7mm (with stand)
			557.3 x 330.4 x 85.8 mm (without stand) 672 x 520 x 228 mm (Package)
Weight		3.6 kg ( net without stand), 7.5 kg (net weight), 11.4 kg (Gross)	
Accessories		DP cable, HDMI cable, USB cable, power adapter, power cord, quick start guide, warranty card, color calibration report, ROG welcome card, ROG sticker	
Compliance and Standards		TUV-Flicker Free, TUV-Low Blue Light, G-Sync, VESA DisplayHDR 400	
** Place he noted that to applie 540 Hz. Nuidia BTY 20 ceries above graphic card is required and current Windows OS ve			

<sup>\*\*</sup> Please be noted that to enable 540 Hz, Nvidia RTX 20 series above graphic card is required and current Windows OS version is limited to 500Hz. For additional information about enabling 540Hz, contact your graphics card manufacturer and Microsoft for more information.

\*\*measuring a screen brightness of 200 nits without audio/ USB/ Card reader connection

<sup>\*\*\*</sup>spec may subject to change until MP